

Desktop Audiovisual All-In-One USB Conferencing Camera

# iconnect

PUS-CC100







ALLOWING YOU & "i"
LOVE TO CONNECT



#### **Product Description**

Desktop Audiovisual All-In-One USB Conferencing Camera it is a powerful and easy-to-use in video conferencing and collaboration device, suitable for individuals and Small Teams & SME Users. It is equipped with SONY 1/2.7" High-quality CMOS senor with 110° Ultra Horizontal of View Angle. Allowing you to capture every details & Contents of meeting with your team with 1080p video

streaming. and iConnect Built-in 4 Elements Beam Forming (BF) microphone array, with a pickup distance of 6 meters, Combine to New Generation AI Sound localization & Learning Technology to improved human-voice-optimized, let you Enjoy outstanding audio clarity, volume and bring you immersed in More Clear & louder and more reality Audio Visual experience.



#### Allows to Enjoy 1080P Full HD Video Conferencing

iConnect allows you to enjoy 1080P full HD video conferencing and content sharing anytime, anywhere, creating barrier-free communication.




#### 110° Ultra-Wide Horizontal of View Angle

Allows you to capture every detail and content of the team meeting.



#### **High-quality Image Streaming**

Equipped with SONY 1/2.7" high-quality CMOS sensor, True color reproduction, Low noise, High-quality image streaming.



#### **Far-field Voice Pickup**

array, with a pickup distance of 6 meters.



#### **Sound Processing Technology**

Built-in 4 Elements Beam Forming (BF) microphone The speaker adopts ANR, AES, AG sound processing technology, and the sensitivity is up to 110dB.







## Plug & Play, General Compatibility With Leading Online Conference Platforms

Plug & play and compatible with all your favorite applications and platforms such as Zoom, Cisco WebEx, Google Hangouts, Microsoft Teams, Vidyo, BlueJeans.











#### You Have It Under Your Control

PUS-CC100 Various methods of control for USB 3.0 Type-C interface.

Compatible with Windows® 7/8/8.1/10 or Mac OS® X 10.7 or higher, Google Chromebook version 29.0.1547.70, Android 5, Linux System.












### **PUS-CC100 Specifications**

Camera		Microphone	Speaker
Sensor	1/2.7" SONY Exmor CMOS	360° Omnidirectional Microphone, Al Sound Localization & Learning Technology	Echo Suppression, Automatic Noise Reduction and Automatic Gain
Lens	F=3.5mm, Fixed Lens		
Minimum Illumination	0.5Lux@ F1.8	Hertz Frequency: 22HZ-17.5KHZ	
		Sensitivity: 30+2dB SPL/mv	Sensitivity: 110dB SPL/mv
Shutter Speed	1-1/10000	4 Elements beam forming microphone array	Maximum output: 110dBSPL
HOV	Approx 110°	The pickup distance is 6 meters	10-stage adjustable
White Balance	Yes	Turn on/off the camera Turn on/off the microphone Increase or decrease the volume	Distortion Rate: <5% @ 220Hz
Interface	USB Type-C		Power Consumption of Horn: 4.5W
Frame Rate		Max 1080p@30fps	
Operating System		Windows® 7/8/8.1/10 or Mac OS® X 10.7 or higher, Google Chromebook version 29.0.1547.70 Android 5, Linux System	
Compatible Applications		Skype ™, Skype for Business, V-CUBE, Google Hangouts ™, FaceTime®, Cisco Webex®, GoToMeeting®, Adobe® Connect ™, BlueJeans, Zoom, Vidyo®, Fuze, WebRTC, CyberLink U Meeting®	
		Generic	
Input Voltage		5V @USB3.0	
Maximum Power		4.5W	
Operating Humiture		-10°C ~+50°C /20%~90%	
G.W		0.95 KGS	
N.W		0.54 KGS	
Packing size (L×W×H)		326mm x 105mm x 102mm	
Inside The Box		PUS-CC100 Desktop Audiovisual All-In-One USB Camera $ imes$ 1, 1.8 meters USB3.0 Type-C cable $ imes$ 1, User Manual / Warranty Information Card $ imes$ 1	

#### **PUS-CC100 Dimension**









Shenzhen PUAS Industrial Co., Ltd

2/F, C/Building, Huawang Industrial Park, Longhua New District, Shenzhen, GD, China



